



1/2" 1.4/6mm C		1/3"	
Focal Length	f=6mm±5%		
Max. Diameter (Ratio)	F=1:1.4±5%		
Element	6 Groups 7 Elements		
Picture Size	4.8x6.4mm		3.6x4.8
Angle	Ver.	44.0°	33.7°
	Hor.	57.3°	44.2°
	Dia.	69.4°	54.4°
Distortion (TV)	-1.0%		
Shooting Range at M.O.D.	Ver.	128mm	
	Hor.	174mm	
	Dia.	221mm	
Minimum Object Distance	0.2m		
Flange Back	17.526mm	in air	
Back Focus	9.46mm in air		
Filter Screw Size	M25.5x0.5		
Front/Rear Effective Dia.	F:φ16.2mm	R:φ8.7mm	
Mount	C-MOUNT		
Exit Pupil	-77.3mm		
Temperature Range	-10~+45° C		
Storage Temperature Range	-40~+60° C		
Resolution	Center:100line/mm	Corner:60line/mm	
Stopper Strength	10kgf·cm		
Endurance Tests	Iris:5,000times	Focus:5,000times	
Operating Torque	Iris:50~600gf·cm	Focus100~1000gf·cm	
Weight	60g±5g		

1/2" 1.4/6mm

LM6NCL

2010.11.09